

★ ★  
STANDARD

## Masonry saw TBE350

Cutting depth up to 110 mm



Swivelling saw head enables 45° mitre cuts



Two robust castors ensure total manoeuvrability in the deployment location



Angle stop provided for cuts of 30° to 90°

The TBE350 table saw offers an uncompromising price-performance ratio as well as high flexibility through numerous settings and application options. A sturdy saw table with

anti-slip support guarantees clean cuts. The swivelling saw head allows mitre cuts to be made with ease. Detachable table feet and transport wheels ensure trouble-free transport.

**TYROLIT**

# System & Accessories

## Technical data

Saw blade	
Max. cutting depth	110 mm
Max. saw blade Ø	400 mm
Cutting length	600 mm
Saw blade speed	2 800 rpm
Saw blade holder Ø	25.4 mm

## Drive

Drive / motor	Electric
Output	2.2 kW
Standard voltage / frequency	230 V / 50 Hz
Optional voltage / frequency	110 V / 60 Hz
Engine cooling	Air cooling
Saw blade drive	Direct

## Design

Ininitely adjustable cutting depths
Angle cutting function (angle stop)
Mitre cutting function (swiveling saw head)
Cap cutting function
Water tank made from powder-coated steel
Electric water pump
Dismantable

## Dimensions & Weight

Length	1 140 mm
Width	640 mm
Height	1 230 mm
Weight	79 kg

## System & Accessories

Masonry saw TBE350	
10981423	Masonry saw TBE350 / 230 V
10981424	Masonry saw TBE350 / 110 V