



Drill motors DME24MW | DME24UW


Core drilling up to Ø 250 mm



Especially compact and light



Performance and service indicator, as well as levelling aid



Time saving drill rig mounting via ModulDrill™ quick change clamping system

The low weight and extremely compact size are the highlights of the DME24 and ensure perfect handling. The mechanical and electronic overload cut-out and the full metal housing ensure high reliability. Built-in

performance and service indicators, as well as the levelling aid, also enable easy operation. The drill motor is available with different drill rig attachments (ModulDrill™ quick clamping system or universal plate).

System & Accessories

Technical data

Drill motors	DME24MW		DME24UW	
	Voltage / Frequency	230 V / 50 Hz	110 V / 60 Hz	230 V / 50 Hz
Type no.	10992081	10992082	10992083	10992084
Drill diameter range	40–250 mm			
Nominal power	2.2 kW			
Nominal current	10 A	20 A	10 A	20 A
Load speed	370/590/990 rpm			
No load speed	710/1 130/1 900 rpm			
Motor cooling	Air			
Tool attachment (external)	1 ¼"			
Tool attachment (internal)	½"			
Operation	Rig-based			
Application	Wet			
Electric overload cut-out	•			
Mechanical overload cut-out	•			
PRCD protection switch	•			
Performance indicator	•			
Service indicator	•			
Drill rig attachment	ModulDrill™	Universal plate		

Dimensions & Weight

Length	465 mm		
Width	115 mm		
Height	175 mm	155 mm	
Weight	7.6 kg	7.7 kg	

System & Accessories

Core drilling system with DRA250 (Steel dowel foot)	
10992081	Electric drill motor DME24MW
10987500	Drill rig DRA250
11002077	Fastening bolt assembly

Core drilling system with DRU250 (Alu. dowel-vacuum foot)

10992081	Electric drill motor DME24MW
10984500	Drill rig DRU250
960795	Vacuum set
10999500	VPE600 Vacuum pump 230V EU/CH
975381	Vacuum hose 3 m complete

Accessories

400439	Extension ½" 100 mm
359475	Extension ½" 200 mm
359476	Extension ½" 300 mm
889232	Extension ½" 400 mm
378198	Extension 1 ¼" 100 mm
359471	Extension 1 ¼" 200 mm
359472	Extension 1 ¼" 300 mm
359473	Extension 1 ¼" 400 mm
359474	Extension 1 ¼" 500 mm
963339	Anti-friction element 1 ¼", max. 2.4 kW
974984	Supporting ring alum. 1 ¼"